212

TEAK OIL SEALER



Description

Step 3: Teak protection.

- 212 saturates and nurishes the wood, it also gives it a hydrophobic treatment (waterproofing).
- Teak will be permanently protected from the elements and, cleaning, especially after the rainy season, will be facilitated.
- The 212 also has the advantage of maintaining the natural aspect of the wood, allowing it to dry quickly, leaving a grease-free surface.

Product information

Composition	Contains n-butyl acetate, Hydrocarbons, C9-C11, n-alkanes, isoalkanes, Cyclics, <2% aromatics, 1-methoxy-2-propanol, monopropylene glycol methyl ether
Appearance/ Odour	Liquid , limpid / solvent
pH	N.A
Density	N.A
Flash point	27°C (80.6°F)
Transport N° ONU	1993
Storage	In its original packaging in a well-ventilated place, away from heat sources.
Packaging	1L

Directions for use

Compatibility / supports	Teak, exotic woods
Méthodes	- 212 is used pure on a clean and dry surface: new teak, sanded or cleaned. - Stir the oil before the application. Apply with a soft brush. Let it rest for at least 6 hours. It is recommended to apply at least two coats for the first treatment. - The following maintenance intervals result in an application approximately every 10 weeks (depending on the ambient pollution, the use and exposure of the bridge). - Between two applications, the bridge may be washed with clear water and a soft brush, with a detergent, if necessary.

Precautions for use



- Dangerous product, respect the direction for use.

Flammable liquid and vapour. May be fatal if swallowed or inhaled.
May cause drowsiness or dizziness.
Before use: Always perform a test in a corner and in a small area.
Keep away from sources of heat and ignition. Direct sunlight.

SAFETY DATA SHEET AVAILABLE ON REQUEST

Always refer to the descriptions on labels. Keep out of reach of children. Respect the conditions of use.

Made in France by Proyacht SARL
460, Av. de la Quiera - 213 Voie E - 06370 Mouans-Sartoux
Tél. : +33 (0) 493 229 865
Clin'Azur & Proyacht are registered trademarks